

**PRODUCT DATASHEET**

# SERIES 1000™

## Oxygen Monitor



FEATURES	BENEFITS
Full three-year sensor warranty	Ensures trouble-free and cost-effective operation when compared to sensors having 6-12 month warranties
Exceptional speed of response	Detects oxygen alarm events in seconds
Extended life oxygen sensor	Eliminates frequent sensor replacement and annoying false low oxygen alarms. Won't fail due to heat fatigue like certain high temperature current limited zirconium oxide sensors.
Economically priced	Saves hundreds of dollars per point
WATCHMAN CIRCUIT™	Alerts users of major status changes in the Series 1000 Oxygen Deficiency Monitor and the environment
CO <sub>2</sub> resistant sensor	Eliminates sample conditioning and premature sensor failures, while minimizing routine maintenance
Extended life sensor with an expected life of five years	Be aware of high temperature current limited zirconium oxide sensors that can prematurely fail due to heat fatigue.
Open sensor diffuser	No dependence on a sample pump or aspirator

## Product Description

The Series 1000™ Oxygen Deficiency Monitor is a popular choice of government labs, universities, and industrial facilities to help ensure the quality of breathing air. The Series 1000 Oxygen Deficiency Monitor's primary use is for applications when the possibility exists that breathing air oxygen could be displaced by stored or piped inert gases such as nitrogen, helium, argon, carbon dioxide, etc. resulting in a hazardous condition.

The Series 1000 Oxygen Deficiency Monitor is a microprocessor-controlled instrument with a range of 0-30%. It is powered from a universal 115-230VAC, 50-60Hz. Oxygen values are displayed on an easy-to-read, 10.2 mm (0.4") high, 4-1/2 digit liquid crystal display (LCD). The Series 1000 Oxygen Deficiency Monitor can be equipped with an optional remote sensor enclosure. The oxygen sensor is mounted in a resilient, polycarbonate electronics enclosure. An optional remote sensor enclosure is available for mounting up to several thousand feet from the monitor. In its standard configuration, the electronics enclosure is rated NEMA 1 (IP 30).

The eloquence of the Series 1000 Oxygen Deficiency Monitor is its ease of use. The electronics and optional remote sensor enclosures are equipped with mounting holes molded into each of the four corners for quick and easy installation. The front panel of the Series 1000 Oxygen Deficiency Monitor contains five switches that provide access to the instrument's settings. The Series 1000 Oxygen Deficiency Monitor is equipped with three oxygen alarm relays and one status alarm relay.

All four relays are Form C (SPDT) types rated at 10 amps at 110/220VAC and 30VDC. The relays are user configurable for fail-safe operation. In addition to the four alarm contacts, the Series 1000 Oxygen Deficiency Monitor has a built-in audible alarm and three red LEDs for visual indication of an oxygen alarm condition. The audible alarm may be manually canceled at any time. If the audible alarm is canceled and the alarm event continues, indications of this condition will still be available through the front panel LEDs and the relay contact(s).

The Series 1000 Oxygen Deficiency Monitor comes equipped with two standard analog outputs: 4-20mADC and 0-2VDC for use with recorders, dataloggers, etc. For enhanced communications, the Series 1000 Oxygen Deficiency Monitor can be configured with optional RS-232C or RS-485 serial communications. For multiple point installations, the RS-485 format provides the capability to send digital signals over greater distances and to control each monitor using the same communications channel.

The sensor in the Series 1000 Oxygen Deficiency Monitor has an open diffuser design and does not require a sample pump or aspiration system. Since the extended life sensor is sealed, it does not require an initial charge of electrolyte, or a periodic "topping off" due to evaporation, as do other types of oxygen sensors. Users do not have to handle caustic electrolyte (a hazardous substance).

## SPECIFICATIONS

### Performance

<b>Measurement Range:</b>	0-30% Oxygen
<b>Accuracy:</b>	±1% of full scale
<b>Response Time:</b>	90% of full scale response in less than 12 seconds
<b>Sensor Type:</b>	Extended life ambient temperature electrochemical type
<b>Temperature &amp; Pressure Compensation:</b>	Standard
<b>Operating Temperature:</b>	5° to 40° C (40° to 104°F)
<b>Product Warranty:</b>	Three years sensor and electronics

---

### Electrical

<b>Display:</b>	10.2 mm (0.4") high, 4-1/2 digit liquid crystal display. Resolution 0.1%.
<b>Input Power:</b>	Universal 115-230VAC, 50-60Hz
<b>Standard Outputs:</b>	4-20mADC and 0-2VDC
<b>Digital Outputs:</b>	Optional RS-232C or RS-485 comm
<b>Oxygen Alarm Relays:</b>	Three (3) SPDT Form C contacts rated 10 A @30VDC/110/220VAC. Alarm clearing is user selectable for either manual or automatic.
<b>Audible Alarm:</b>	Internal buzzer
<b>Audible Alarm Cancel:</b>	Front panel
<b>Instrument Status Alarm Relay:</b>	Front panel 1 SPDT Form C rated identical to above

---

### Construction

<b>Electronics Control Unit:</b>	Light gray polycarbonate with a hinged clear front cover. Rated NEMA 1 (IP 30).
<b>Electronics Control Unit Dimension*:</b>	9.44 in. (239.8 mm) length 6.29 in. (159.8 mm) width 3.54 in. (89.9 mm) height
<b>Sensor Mounting:</b>	Either in the electronics enclosure or remotely
<b>Sensor Inputs:</b>	One
<b>Optional Remote Sensor Enclosure Dimensions*:</b>	Light gray polycarbonate rated NEMA Sensor Enclosure: 1 (IP 30) 4.72 in.(119.9 mm) length 3.14 in.(79.8 mm) width 3.34 in. (84.8 mm) height
<b>Weight (Control Unit):</b>	4.08 kg. (9 lbs.)
<b>(Remote Sensor):</b>	<0.45 kg (<1 lb.)

\* Note: All dimensions are without optional equipment

## GAIN REAL-TIME INSIGHT INTO YOUR PROCESS

Process Insights manufactures and delivers premium sensors, monitors, detectors, analyzers, instrumentation, and software that are mission-critical to keep your operations, personnel, and the environment safe – every day across the globe.

Get the most reliable, precision analytical technologies available on the market today. We will work to match your needs and budget, and provide the optimal, and most stable process analysis solution for your application.

---

## CENTERS OF EXCELLENCE | PROVIDING PROVEN SOLUTIONS

Process Insights is committed to solving our customers' most complex analytical, process, and measurement challenges everyday.

### Process Insights – The Americas

4140 World Houston Parkway Suite 180, Houston, TX 77032, USA +1 713 947 9591

### Process Insights – EMEA

ATRICOM, Lyoner Strasse 15, 60528 Frankfurt, Germany +49 69 20436910

### Process Insights – APAC


Wujiang Economic and Technology, Development Zone, No. 258 Yi He Road, 215200 Suzhou, Jiangsu Province, China +86 400 086 0106

---

For a complete range of products, applications, systems, and service options, please contact us at: [info@process-insights.com](mailto:info@process-insights.com)

For a complete list of sales & manufacturing sites, please visit: <https://www.process-insights.com/about-us/locations/>

COSA Xentaur, Tiger Optics, Extrel, Alpha Omega Instruments, ATOM Instrument, MBW Calibration, MGA, Guided Wave, ANALECT and LAR TOC Leader are trademarks of Process Insights, Inc.



REVOLUTIONIZING MEASUREMENT

**EVERYWHERE**