

PRODUCT DATASHEET

SERIES 2500 & 2510™

Percent Oxygen Transmitter



Product shown with optional flow meter, needle valve and coalescing filter



| FEATURES | BENEFITS |
|-----------------------------------|--|
| Wide Number of Ranges | Measure from <0.1% to 100% Oxygen |
| Exceptional Speed of Response | Responds Instantaneously to Changes in Oxygen |
| Rugged and Versatile Construction | NEMA 4 Housing Withstands Harsh Environments |
| Economically Priced | Save Thousands of Dollars vs Other Methods |
| Extended Life Sensor | Eliminates Frequent Sensor Replacement |
| Acid Gas Resistant Sensor | Eliminates Sample Conditioning for Many Applications |
| Factory Calibration | Factory calibration and certificate included at no additional charge |

Product Description

The Series 2500™ Trace Oxygen Transmitter is a true loop powered (14-32 VDC) percent oxygen transmitter designed to provide accurate and dependable percent oxygen measurements in a variety of background gases. Measurement ranges available are from 0-2% to 0-100%. The Series 2500 enclosure is made from durable polycarbonate, and is rated for NEMA 4 (IP 66) service (may change with the addition of certain optional equipment). A 4-20 mA DC output is provided that can be used with a data logger, recorder, PLC, DCS, etc. Options include pressure regulators, flow meters, sample filters, sample pumps, and explosion proof (NEMA 7) housings.

The Series 2510 Percent Oxygen Transmitter is the AC powered (115 or 230 VAC, 50-60 Hz) or 24VDC counterpart to the Series 2500 and is recommended when AC power is available

or preferred.

The Series 2500 and Series 2510 Percent Oxygen Transmitters feature an extended life oxygen sensor with EES (enhanced electrolyte system). This sensor provides exceptional performance, accuracy, and stability. For applications where carbon dioxide is present in the sample gas, the EES retards passivation of the sensor anode by allowing the products of oxidation to dissolve in the electrolyte. In effect, the sensor is renewed continuously, resulting in an increase in sensor life even if exposed to 100% carbon dioxide. In addition, the enhanced mechanical design of the sensor ensures longer life, and virtually eliminates leakage of electrolyte, a nagging (and expensive) problem associated with sensors that require periodic electrolyte maintenance.

SPECIFICATIONS

Performance

Measurement Ranges

in Percent:

0-2/100

0-5/100

0-10/100

0-25/100

0-100/10

Switchable Range (Calibrated on the first range)

Accuracy¹:

±1% of full scale (± 5% of full scale on ranges ≤ 0-5%)

Linearity:

±1% of full scale

Response Time:

90% of full scale response in less than 20 seconds (typical)

Sensor Type:

Long-life electrochemical sensor

Temperature Compensation:

Standard

Operating

Temperature Range:

40° to 104° F (5° to 40°C)

Warranty:

2 years electronics/1 year sensor

Electrical

Series 2500 Loop Powered Trace

Oxygen Transmitter: Input power 14-32 VDC

Series 2510 Trace

Oxygen Transmitter: Input power 115 or 230 VAC, 50-60 Hz, or 24 VDC

Input Power: Universal 115-230VAC, 50-60Hz or 18-32 VDC

Analog Output: 4-20mADC with a loop resistance of 600 ohms@ 24VDC
(consult factory for other resistance values)

Sample Gas Characteristics

Sample Flow Rate: 1.0 to 2.0 SCFH (0.5 to 1.0 liter/min)

**Sample Gas
Temperature:** 40° to 104°F (5° to 40°C)

Sample Gas (0.007 to 0.1 kg/cm²)

Construction

Enclosure: Polycarbonate, rated NEMA 4X (IP66) without optional equipment. NEMA 7 (explosion proof) optional.

Dimensions*: 6.5 in. (165.1 mm) height
7.0 in. (177.8 mm) width
3.9 in.(99.06 mm) depth

Gas Connections: Quick connect 1/4" OD for plastic tubing or stainless steel compression fittings for installations with metal sample lines

¹ Stated at constant temperature and constant pressure.

* Note: All dimensions are without optional equipment

GAIN REAL-TIME INSIGHT INTO YOUR PROCESS

Process Insights manufactures and delivers premium sensors, monitors, detectors, analyzers, instrumentation, and software that are mission-critical to keep your operations, personnel, and the environment safe – every day across the globe.

Get the most reliable, precision analytical technologies available on the market today. We will work to match your needs and budget, and provide the optimal, and most stable process analysis solution for your application.

CENTERS OF EXCELLENCE | PROVIDING PROVEN SOLUTIONS

Process Insights is committed to solving our customers' most complex analytical, process, and measurement challenges everyday.

Process Insights – The Americas

4140 World Houston Parkway Suite 180, Houston, TX 77032, USA +1 713 947 9591

Process Insights – EMEA

ATRICOM, Lyoner Strasse 15, 60528 Frankfurt, Germany +49 69 20436910


Process Insights – APAC

Wujiang Economic and Technology, Development Zone, No. 258 Yi He Road, 215200 Suzhou, Jiangsu Province, China +86 400 086 0106

For a complete range of products, applications, systems, and service options, please contact us at: info@process-insights.com

For a complete list of sales & manufacturing sites, please visit: <https://www.process-insights.com/about-us/locations/>

COSA Xentaur, Tiger Optics, Extrel, Alpha Omega Instruments, ATOM Instrument, MBW Calibration, MGA, Guided Wave, ANALECT and LAR TOC Leader are trademarks of Process Insights, Inc.



REVOLUTIONIZING MEASUREMENT

EVERYWHERE