

**PRODUCT DATASHEET**

# 9800 Calorimeter™

Zero Hydrocarbon Emissions –  
Injection Measurement Calorimeter



## Zero Hydrocarbon Emissions

## Accurate Measurements

## Low Maintenance

- Flare Stack Control
- Fuel Optimization
- Gas Blending
- Custody Transfer
- Flare Monitoring
- Biogas
- Natural gas
- Refinery gas
- Furnace at 1000°C for complete combustion
- BTU without the need for a Specific Gravity Cell
- O<sub>2</sub> Cell mounted outside of furnace
- Direct Measurement of BTU/SCFH
- Wall mounted
- Small footprint


## 9800 Calorimeter

- Zero HC Emission
- Fast Response Injection Style
- Direct Measurement of Calorific Heating Value
- BTU Measurement Range 0-3000 BTU/scfh
- Handles High Sulfur Concentrations
- H<sub>2</sub> Measurement Option
- Industrial PLC System, Touchscreen HMI
- High Temperature Combustion
- Flameless / No Flameouts
- Built for Indoor, Outdoor, Dirty, and Corrosive Environment
- Precise Measurement of Air Fuel Ratio

### Measurement Principle: Residual Oxygen Measurement

The 9800™ Calorimeter uses the measuring principle based on the analysis of the residual oxygen content in fuel or flare gas after combustion of the sample. A small constant volume of sample gas is injected into a continuous flow of combustion air with each measurement cycle, providing a precisely maintained fuel/air ratio profile.

The fuel air mixture is oxidized in the combustion furnace at 1000°C, and the residual oxygen concentration of the combustion sample is measured by a zirconia oxide sensor. The residual oxygen provides an accurate method of measuring Heating Value with optional measurement of Wobbe Index correlated to Specific Gravity of the sample gas. Higher temperature reduces maintenance of the instrument; varying temperature up to 1000°C.



The majority of the sample gas will return to the process gas stream through the fast loop so there is no hazardous hydrocarbon emission. Only the small amount of sample gas and air mixture is completely burned in the combustion process resulting in extremely low, non-hazardous (CO<sub>2</sub>) emissions.

### Additional Features

- Compact, sturdy O<sub>2</sub> Cell is designed to be cost-effective, and for ease of maintenance and service
- Internal sample system up to 50°C with options to 100°C or 150°C
- Full measurement range 0-3000 BTU/SCFH without the need of a specific gravity meter

### Higher Temperatures, Reliability Improvements

The 9800 Calorimeter maintenance requirements are low. It's easy to maintain. The zirconia oxide sensor is mounted in the electronics cabinet for added safety and speedy access.

Higher furnace temperatures provide complete oxidization of any molecular-bound sulfur compounds, virtually eliminating the typical accumulation of uncombusted sulfur products in the furnace vent further reducing instrument maintenance. Combined with use of proper sample conditioning, the 9800 Calorimeter can operate unattended for several months. All compartments are easily accessible through separate doors on the front side of the enclosure.

# SPECIFICATIONS

Analyzer Performance:	
Model	9800 Calorimeter
Sample gas	Natural gas, fuel gas, refinery gases, biogas, flare gas, etc.
Ranges	Heating Value: 0-3000 BTU/SCF, Wobbe Index: 0-2750 BTU/SCF, CARI Index: 0-20
Accuracy	± 1% full scale
Repeatability	±0.5% BTU/SCF
Response Time	< 30 sec
Ambient temperature	Base: 5°C (41°F) to +40°C (104°F), -20°C (-4°F) to +55°C (104°F)
Outputs	(optional) 4 Analog Outputs, 4 Digital Outputs, 2 (optional)
Communication	Modbus over TCP/IP
Specific Gravity (optional)	Range: 0.2-2.2 RD
Enclosure	IP65 NEMA 4X
Furnace Temperature	Up to 1000°C
Utilities:	
Power supply	110/220 V AC, 50/60 HZ
Power consumption	2000 V A Base
Air Consumption	180 SCFH (Analyzer), 296 SCFH (with Purge) @ 80 psig
Sample	Sample usage 100cc/min
Sample Pressure	5-100 psig
Mounting	Wall mount with optional stand or cart available
Weight	200 lbs. (91k kg)
Dimensions	30" H x 40" W x 14" D (762 mm x 1016 mm x 356 mm)



All features, functionality and other product specifications are subject to change without notice or obligation.

## Analyzer Construction

The 9800 Calorimeter is housed in a powder coated NEMA4x (IP65) cabinet suitable for outdoor installations without additional temperature controlled shelter. For extreme climate conditions, the standard operating temperature range of the 9800 Calorimeter can be extended with the addition of a cabinet heater and/or vortex cooler. Enclosure is wall mounted with optional stand.

The analyzer cabinet has three compartments: the gas mixing compartment, the combustion furnace compartment, and the electronics compartment.



The **Sample Conditioning Enclosure** contains sample conditioning and the gas mixing system. Components in this compartment are intrinsically safe. The gas mixing compartment is heated to avoid condensation of heavier gas constituents.

The **Combustion Furnace Enclosure** contains the combustion furnace and the zirconia oxide sensor is located separately in electronics cabinet. Both electronics compartment and combustion furnace compartment can optionally be purged for Class 1 Div 2 applications.

The **Electronics Enclosure** contains the industrial PLC system and touchscreen HMI, which performs all instrument control functions and calculations. Results are available through digital and analog outputs and a touchscreen HMI, which displays Heating Values and Wobbe Index in BTU/SCF or MJ/Nm<sup>3</sup>, residual O<sub>2</sub> in %, Cell voltage in mV, relative density (optional), and CARI (Combustion Air Requirement Index).

## GAIN REAL-TIME INSIGHT INTO YOUR PROCESS

Process Insights manufactures and delivers premium sensors, monitors, detectors, analyzers, instrumentation, and software that are mission-critical to keep your operations, personnel, and the environment safe – every day across the globe.

Get the most reliable, precision analytical technologies available on the market today. We will work to match your needs and budget, and provide the optimal, and most stable process analysis solution for your application.

---

## CENTERS OF EXCELLENCE | PROVIDING PROVEN SOLUTIONS

Process Insights is committed to solving our customers' most complex analytical, process, and measurement challenges everyday.

### Process Insights – The Americas

4140 World Houston Parkway Suite 180, Houston, TX 77032, USA +1 713 947 9591

### Process Insights – EMEA

ATRICOM, Lyoner Strasse 15, 60528 Frankfurt, Germany +49 69 20436910

### Process Insights – APAC


Wujiang Economic and Technology, Development Zone, No. 258 Yi He Road, 215200 Suzhou, Jiangsu Province, China +86 400 086 0106

---

For a complete range of products, applications, systems, and service options, please contact us at: [info@process-insights.com](mailto:info@process-insights.com)

For a complete list of sales & manufacturing sites, please visit: <https://www.process-insights.com/about-us/locations/>

COSA Xentaur, Tiger Optics, Extrel, Alpha Omega Instruments, ATOM Instrument, MBW Calibration, MGA, Guided Wave, ANALECT and LAR TOC Leader are trademarks of Process Insights, Inc.



REVOLUTIONIZING MEASUREMENT

**EVERYWHERE**