

PRODUCT DATASHEET

HALO LP H₂O™

TRACE MOISTURE IN HYDRIDE GASES



HALO LP H₂O offers:

- Low parts per billion (ppb) moisture detection capability in NH₃ and PH₃
- Absolute measurement (freedom from calibration gases)
- Wide dynamic range – over four orders of magnitude
- Low cost of ownership and operational simplicity
- Clean technology – no external calibration gases required
- Compact analyzer footprint
- User-programmable alarms immediately notify on high events

Specifications

Performance

Operating range:	See gas performance table below
Detection limit (LDL, 3σ/24h):	See gas performance table below
Precision (1σ, greater of):	$\pm 1\%$ or 1/3 of LDL
Accuracy (greater of):	$\pm 4\%$ or LDL
Speed of response:	< 3 minutes to 95%
Environmental conditions:	10°C to 40°C 30% to 80% RH (non-condensing)
Storage temperature:	-10°C to 50°C

Gas Handling System and Conditions*

Wetted materials:	316L stainless steel (corrosive gas version optional) 10 Ra surface finish
Gas connections:	1/4" male VCR inlet and outlet
Leak tested to:	1 x 10 ⁻⁹ mbar l / sec
Inlet pressure:	10 – 125 psig (1.7 – 9.6 bara)
Outlet pressure:	<10 Torr (13 mbar)
Flow rate:	Up to 1.0 slpm
Sample gases:	NH ₃ , PH ₃ , AsH ₃ & inert matrices
Gas temperature:	Up to 60°C

Dimensions & Weight

Standard sensor (incl. shutoff valves):	H x W x D 8.73 x 8.57 x 26.4 in (222 x 218 x 670 mm)
Sensor rack (fits up to two sensors):	H x W x D 8.73 x 19.0 x 26.4 in (222 x 483 x 670 mm)
Standard sensor weight:	33 lbs (15.0 kg)

Electrical and Interfaces

Platform:	Max Series analyzer
Alarm indicators:	2 user programmable 1 system fault Form C relays
Power requirements:	90 – 240 VAC, 50/60 Hz
Power consumption:	40 Watts max. (excluding vacuum pump)
Signal output:	Isolated 4–20 mA
User interfaces:	5.7" LCD touchscreen. 10/100 Base-T Ethernet. USB, RS-232, RS-485. Modbus TCP (optional)
Data storage:	Internal or external flash drive
Certification:	CE Mark

*Vacuum source required

Standard Model

Performance, H₂O

	Range	LDL (3σ)	Precision (1σ) @ zero
In Ammonia:	0 – 20 ppm	9 ppb	3 ppb
In Phosphine [†] :	0 – 10 ppm	9 ppb	3 ppb
In Nitrogen:	0 – 6 ppm	1.0 ppb	0.3 ppb
In Argon:	0 – 4 ppm	0.8 ppb	0.25 ppb
In Hydrogen [†] :	0 – 6 ppm	1.0 ppb	0.3 ppb
In Helium:	0 – 3 ppm	0.6 ppb	0.2 ppb
In NO [†] :	0 – 100 ppm	16 ppb	6 ppb
In Germane [†] :	0 – 18 ppm	20 ppb	7 ppb

Arsine Model

Performance, H₂O

	Range	LDL (3σ)	Precision (1σ) @ zero
In Arsine [†] :	0 – 10 ppm	5 ppb	2 ppb
In Nitrogen:	0 – 6 ppm	1.0 ppb	0.3 ppb
In Argon:	0 – 4 ppm	1.0 ppb	0.3 ppb
In Hydrogen [†] :	0 – 6 ppm	1.0 ppb	0.3 ppb
In Helium:	0 – 3 ppm	1.0 ppb	0.3 ppb

[†]Low leak rate vacuum pump (safety certified for service in relevant gas) required.

Contact us for additional analytes and matrices.
U.S. Patent # 7,277,177

GAIN REAL-TIME INSIGHT INTO YOUR PROCESS

Process Insights manufactures and delivers premium sensors, monitors, detectors, analyzers, instrumentation, and software that are mission-critical to keep your operations, personnel, and the environment safe – every day across the globe.

Get the most reliable, precision analytical technologies available on the market today. We will work to match your needs and budget, and provide the optimal, and most stable process analysis solution for your application.

CENTERS OF EXCELLENCE | PROVIDING PROVEN SOLUTIONS

Process Insights is committed to solving our customers' most complex analytical, process, and measurement challenges everyday.

Process Insights – The Americas

4140 World Houston Parkway Suite 180, Houston, TX 77032, USA +1 713 947 9591

Process Insights – EMEA

ATRICOM, Lyoner Strasse 15, 60528 Frankfurt, Germany +49 69 20436910


Process Insights – APAC

Wujiang Economic and Technology, Development Zone, No. 258 Yi He Road, 215200 Suzhou, Jiangsu Province, China +86 400 086 0106

For a complete range of products, applications, systems, and service options, please contact us at: info@process-insights.com

For a complete list of sales & manufacturing sites, please visit: <https://www.process-insights.com/about-us/locations/>

COSA Xentaur, Tiger Optics, Extrel, Alpha Omega Instruments, ATOM Instrument, MBW Calibration, MGA, Guided Wave, ANALECT and LAR TOC Leader are trademarks of Process Insights, Inc.



REVOLUTIONIZING MEASUREMENT

EVERYWHERE