

PRODUCT DATASHEET

HALO™ QRP

TRACE-LEVEL LOW-PRESSURE MOISTURE ANALYZER



Designed for trace level moisture analysis in low pressure (<50 Torr) applications, the HALO QRP offers:

- Detection limit of 1 μ Torr partial pressure H₂O and below
- Absolute accuracy and excellent precision
- Wide dynamic range – over four orders of magnitude
- Low cost of ownership and operational simplicity
- Clean technology – no external calibration gases required
- Compact analyzer footprint, ideal for OEM equipment integration

Protect Your Process with the HALO QRP

Modern semiconductor deposition processes – from low-temperature epitaxy to ALD and MOCVD – operate routinely at chamber pressures far below atmosphere and approach the single-digit torr range. At the same time, process temperatures are steadily decreasing. Under these conditions, residual moisture in the chamber poses a significant threat to process quality and production yields.

The HALO QRP is optimized to operate under these low-pressure conditions and deliver exact and reliable real-time measurements to verify moisture residue in, for example, the load lock, transfer and process chambers before H₂O contaminants compromise the subsequent process step. Based on proven Cavity Ring-Down Spectroscopy (CRDS) technology, the HALO QRP sets new standards in ease-of-use and measurement precision for this application, and operates at chamber pressures as low as 1 Torr.

Specifications

Performance, H₂O Detection

Operating range:	0 – 12 mTorr _{pp} (1200 ppm @ 10 Torr)
Detection limit (LDL, 24h peak-to-peak variation):	1 µTorr _{pp} (see chart below for ppb units)
Sensitivity (3σ)	0.5 µTorr _{pp} (see chart below for ppb units)
Precision (1σ, greater of):	± 1% or 1/3 of Sensitivity
Accuracy (greater of):	± 5% or 1/2 of LDL
Speed of response:	1 to 2 min (if not flow-limited)
Environmental conditions:	10°C to 40°C, 30% to 80% RH (non-condensing)
Storage temperature:	–10°C to 50°C

Gas Handling System and Conditions*

Wetted materials:	316L stainless steel (corrosive gas version optional), 10 Ra surface finish
Gas connections:	1/4" male VCR inlet and outlet with manual shut-off valves
Leak tested to:	1 x 10 ⁻⁹ mbar l / sec
Inlet pressure[†]:	1 – 1000 Torr
Outlet pressure:	<20 mTorr (0.027 mbar)
Sample gases[§]:	N ₂ , H ₂ , HCl, Ar (standard), He, Cl ₂ (optional)
Gas temperature:	Up to 60°C (in detection cell)

Dimensions & Weight

Standard sensor (incl. shutoff valves):	H × W × D: 8.73 x 8.57 x 26.4 in (222 x 218 x 670 mm)
Sensor rack (fits up to two sensors):	H × W × D: 8.73 x 19.0 x 26.4 in (222 x 483 x 670 mm)
Standard sensor weight:	30 lbs (13.6 kg)

Electrical and Interfaces

Platform:	Max series analyzer
Alarm indicators:	2 user programmable, 1 system fault, Form C relays
Power requirements:	90 – 240 VAC, 50/60 Hz
Power consumption:	40 Watts max.
Signal output:	Isolated 4–20 mA
User interfaces:	5.7" LCD touchscreen, 10/100 Base-T Ethernet USB, RS-232, RS-485, Modbus TCP (optional)
Data storage:	Internal or external flash drive
Certification:	CE Mark


* Vacuum source required

† Pressure requirements for moisture measurement – for gas purge in standby mode, inlet pressure limit is 15 psig (1500 Torr)

§ HCl and Cl₂ sample gases may require corrosive gas version, please contact us for more information.

Contact us for additional analytes and matrices.

U.S. Patent # 7,277,177



Detection limit and sensitivity in concentration units (ppb)

GAIN REAL-TIME INSIGHT INTO YOUR PROCESS

Process Insights delivers premium analytical sensors, analyzers, instrumentation, software and solutions that are mission-critical to keep your operations, personnel, and the environment safe. Our commitment to customer satisfaction is evident through our diverse range of products, programs, and services, designed to accommodate various budgets and application needs.

CENTERS OF EXCELLENCE | PROVIDING PROVEN SOLUTIONS

Process Insights – The Americas

14400 Hollister Street, Suite 800B, Houston, TX 77066, USA +1 713 947 9591
info.americas@process-insights.com

Process Insights – EMEA

ATRICOM, Lyoner Strasse 15, 60528 Frankfurt, Germany +49 69 20436910
info.emeai@process-insights.com

Process Insights – APAC

Wujiang Economic and Technology, Development Zone, No. 258 Yi He Road, 215200 Suzhou, Jiangsu Province, China +86 400 086 0106
info.apac@process-insights.com
info.cn@process-insights.com

For a complete list of sales & manufacturing sites, please visit:
<https://www.process-insights.com/about-us/locations/>

