

HIGH-PERFORMANCE GAS ANALYZERS

#### **PRODUCT DATASHEET**

# HALO KA Max<sup>™</sup>

# THE ULTIMATE TRACE GAS ANALYZER



# HALO KA Max offers:

- Available for detecting trace moisture (H<sub>2</sub>O), ammonia (NH<sub>3</sub>), or methane (CH<sub>4</sub>)
- Parts per trillion (ppt) detection capability in an array of gases
- Absolute measurement (freedom from calibration)
- Field proven lowest Cost of Ownership and ease of use

- Wide dynamic range over four orders of magnitude
- Unprecedented speed of response at sub-ppb levels
- Compact footprint (two HALO KA Max fit in a 19" rack)

# Specifications

#### Performance

Operating range: Detection limit (LDL)\*: Precision (1o, greater of): Accuracy (greater of): Speed of response: Environmental conditions: Storage temperature: See gas performance table on next page See gas performance table on next page  $\pm 0.75\%$  or see tables on next page  $\pm 4\%$  or LDL < 2 min to 95% (for H<sub>2</sub>O/NH<sub>3</sub>), < 1 min to 95% (for CH<sub>4</sub>) 10°C to 40°C, 30% to 80% RH (non-condensing) -10°C to 50°C

### **Gas Handling System and Conditions**

Gas connections:1/4" male VCR inlet and outletLeak tested to: $1 \times 10^{-9}$  mbar l / secInlet pressure:10 - 125 psig (1.7 - 9.6 bara)Flow rate: $\sim 2$  slpm in N<sub>2</sub> (gas dependent)Sample gases:See tables belowGas temperature:Up to  $60^{\circ}$ C

#### **Dimensions & Weight**

Standard sensor: $H \times W \times D \ 8.73 \times 8.57 \times 23.6$  in (222 x 218 x 599 mm)Sensor rack (fits up to two sensors): $H \times W \times D \ 8.73 \times 19.0 \times 23.6$  in (222 x 483 x 599 mm)Standard sensor weight:28 lbs (12.7 kg)NH<sub>3</sub> & H<sub>2</sub>O in CO<sub>2</sub> sensor weight:32 lbs (14.5 kg)

#### **Electrical and Interfaces**

Platform:	Max Series analyzer		
Alarm indicators:	2 user programmable, 1 system fault, Form C relays		
Power requirements:	90 – 240 VAC, 50/60 Hz		
Power consumption:	40 Watts max.		
Signal output:	Isolated 4–20 mA		
User interfaces:	5.7" LCD touchscreen, 10/100 Base-T Ethernet, USB, RS-232, RS-485, Modbus TCP (optional)		
Data storage:	Internal or external flash drive		
Certification:	CE Mark		

# HALO KA Max $H_2O$ **Standard Model**

Performance, H <sub>2</sub> O	Range	LDL <sup>*,†</sup>	Precision (1σ) @ zero
In Nitrogen:	0 – 5 ppm	100 ppt	40 ppt
In Helium:	0 – 1 ppm	100 ppt	10 ppt
In Argon:	0 – 2 ppm	100 ppt	20 ppt
In Hydrogen:	0 – 4 ppm	100 ppt	30 ppt
In Oxygen:	0 – 2.5 ppm	100 ppt	20 ppt
In Clean Dry Air (CDA):	0 – 4 ppm	100 ppt	30 ppt

HALO KA Max H <sub>2</sub> O CO <sub>2</sub> Model Performance, H <sub>2</sub> O In Carbon Dioxide: In Nitrogen:	<b>Range</b> 0 – 10 ppm 0 – 5 ppm	<b>LDL</b> *,† 300 ppt 100 ppt	<b>Precision (1σ) @ zero</b> 100 ppt 40 ppt
HALO KA Max NH <sub>3</sub> Performance, NH <sub>3</sub> In Nitrogen:	<b>Range</b> 0 – 7 ppm	<b>LDL<sup>†</sup> (3σ/24h)</b> 100 ppt	<b>Precision (1σ) @ zero</b> 40 ppt
HALO KA Max CH <sub>4</sub> Performance, CH <sub>4</sub> In Nitrogen: In Helium: In Argon: In Hydrogen: In Oxygen: In Clean Dry Air (CDA):	<b>Range</b> 0 – 8 ppm 0 – 5 ppm 0 – 7 ppm 0 – 8 ppm 0 – 8 ppm	<b>LDL<sup>†</sup> (3σ/24h)</b> 500 ppt 400 ppt 450 ppt 500 ppt 500 ppt 500 ppt	<b>Precision (1σ) @ zero</b> 200 ppt 140 ppt 150 ppt 200 ppt 200 ppt 200 ppt

\*The Detection limit (LDL) is defined as 3σ over 24 hours or the H<sub>2</sub>O drydown limit, whichever is higher. <sup>†</sup>Lowest achievable impurity level is dependent upon the quality of the sample gas and the integrity of the sampling system.

Contact us for additional analytes and matrices. U.S. Patent # 7,277,177



### GAIN REAL-TIME INSIGHT INTO YOUR PROCESS

Process Insights delivers premium analytical sensors, analyzers, instrumentation, software and solutions that are mission-critical to keep your operations, personnel, and the environment safe. Our commitment to customer satisfaction is evident through our diverse range of products, programs, and services, designed to accommodate various budgets and application needs.

# CENTERS OF EXCELLENCE | PROVIDING PROVEN SOLUTIONS

#### **Process Insights – The Americas**

14400 Hollister Street, Suite 800B, Houston, TX 77066, USA +1 713 947 9591

#### **Process Insights – EMEA**

ATRICOM, Lyoner Strasse 15, 60528 Frankfurt, Germany +49 69 20436910

#### Process Insights – APAC

Wujiang Economic and Technology, Development Zone, No. 258 Yi He Road, 215200 Suzhou, Jiangsu Province, China +86 400 086 0106

For a complete range of products, applications, systems, and service options, please contact us at: info@process-insights.com

For a complete list of sales & manufacturing sites, please visit: https://www.process-insights.com/about-us/locations/

