


PRODUCT DATASHEET

MAX300-RTG™ 2.0

Real-time Gas Analyzer with Touch Screen Interface



**Continuous,
real-time analysis**

**Full, speciated
composition**

**High sensitivity
and wide
dynamic range**

- Fast analysis for advanced process control, environmental compliance, and life safety monitoring
- Complete quantitative stream composition: total application coverage with fewer analyzers required
- Multi-port stream selector for up to 160+ samples
- Low maintenance and easy to operate with simple touch screen interface
- Industry-best customer support and application team

SPECIFICATIONS

System Highlights:	
Detectable compounds	Any gas or vapor sample
Integrated touch screen	15" display Customizable and interactive Full Access to Questor5 software
Detection range	– Faraday detector: 100% – 5 ppm – Electron multiplier: 100% – 5 ppb* – Membrane inlet: 100% – 10 ppt*
Number of sample streams	16, 31, 40, 80, 120, 160+
Analysis rate	0.1 – 16 seconds per component Customizable
Number of components	Unlimited
Number of analysis routines	Unlimited
Number of user configurable data tags	Unlimited
Precision	<0.05% RSD over 24 hours**
Stability	<0.5% RSD over 30 days**
Filaments	Two, one active and one spare with automatic switchover
Analyzer maintenance	1-3 years†
Roughing pump	6-12 months†
Manual or fully automated calibration and validation	3-12 month calibration intervals
Mass range options	1 to 250, 300, or 500 amu
Mass filter	19mm quadrupole for high precision, sensitivity and stability

* Matrix dependent. Documented on trace air components and benzene.

** Based on the analysis of 1% argon, scan speed 1 second per analysis.

† Application dependent.

MAX300-AIR System Specifications

Power Supply Options:

- 115 VAC (+/- 10%), 50/60 Hz, Two 20 Amp Circuits
- 230 VAC (+/- 10%), 50/60 Hz, One 20 Amp Circuit

Power Consumption:

- Nominal 2740 Watts
- Heat Load: 2991 Watts (10,200 BTU/hour)

Weight:

- Standard Enclosure: 450 lbs (205 kg)*
- Optional cart: 40 lbs (18 kg)

Ambient Requirements:

- Temperature: -4°F to 120°F (-20°C to 49°C)
- With A/C, cold start $\geq 54^\circ\text{F}$ (12°C)

Area Classification Options:



- General Purpose
- Class 1, Division 2, Groups A,B,C,D, T4 or T3
- IEC/ATEX, Zone 2, Group IIC or IIB +H2*, T3 or T4

Additional Utilities:

- Purge gas (for hazardous area installations)
- Calibration gas cylinders: minimum 2*

Data System and Communications:

- External Control Interface: Modbus (TCP/IP, Fiber Optics, Serial) or Analog Input
- Login security levels: Administrator, User, Viewer
- External Communications: Modbus (TCP/IP or Serial), Analog and Digital I/Os, Fiber Optics



MAX300-RTG 2.0 enclosure with Cart.
Dimensions shown in inches [mm]

*Configuration dependent

Exceptional Worldwide Service and Support

For over 50 years, we have been committed to providing the highest quality support services for the thousands of instruments installed worldwide. Factory trained and certified personnel offer industry-leading support to our customers at every stage of process development and manufacturing.

GAIN REAL-TIME INSIGHT INTO YOUR PROCESS

Process Insights delivers premium analytical sensors, analyzers, instrumentation, software and solutions that are mission-critical to keep your operations, personnel, and the environment safe. Our commitment to customer satisfaction is evident through our diverse range of products, programs, and services, designed to accommodate various budgets and application needs.

CENTERS OF EXCELLENCE

Process Insights – The Americas

14400 Hollister Street, Suite 800-B, Houston, TX 77066, USA

☎ +1 713 947 9591

info.americas@process-insights.com

Process Insights – EMEAI

ATRICOM, Lyonerstrasse 15, 60528 Frankfurt, Germany

☎ +49 69 20436910

info.emeai@process-insights.com

Process Insights – CHINA

Wujiang Economic and Technology, Development Zone No. 258 Yi He Road
215200 Suzhou, Jiangsu Province, China

☎ +86 400 086 01

info.cn@process-insights.com

Process Insights – APAC

Premier@Kaki Bukit, 10 Kaki Bukit Ave 4, Blk 10 #05-65, Singapore 415874

☎ +65 6489 6612

info.apac@process-insights.com

